



Optional fixing holes  
6XNo. 5 self tapping screw  
or tapped to M5X6.0

Ø 12.0mm clearance holes

Required space for lid operation

Required space for lock operation

D:\Solid-Models\Boxer\Peri 4000\

### Thoelen Pumpen GmbH

Tel. 0049 (2832) 80950  
Fax 0049 (2832) 899625 Singendonkskamp 1, D-47626 Kevelaer, Germany

TOOLING OR PRODUCTION SHOULD NOT START PRIOR TO APPROVAL OF THIS DRG. BY THE CLIENT

TOL: Y.X = +/-0.2 Y.XX = +/-0.1
ANGULAR +/- 1deg
REVISIONS
ISS G
ISS F
ISS E
ISS D
ISS C
ISS B

DRG.NO.:	TOL: Y.X = +/-0.2 Y.XX = +/-0.1	ANGULAR +/- 1deg
PART NAME: Thoelen GA	SCALE: 1:2	
PROJECT: TP 4000		
DRAWN: Uri	CHECKED:	
ISS A DATE: 07 November 2007 12:18:53	APPROVED:	
FINISH:		
MATERIAL:	VOLUME:	
COLOUR		



THIRD ANGLE PROJECTION

ALL DIMS> IN mm